

PTR-TOF 1000 ULTRA



Compact ultra-sensitive PTR-TOFMS - Trace VOC Analyzer

Sensitivity > 30000 cps/ppbv LoD < 5 pptv Resolution > 1500 m/Δm

The PTR-TOF 1000 *ultra* is the new benchmark for reliable & ultra-sensitive real-time organic trace gas analyzers.

Based on the successful PTR-TOF 1000 series platform, the PTR-TOF 1000 *ultra* offers all benefits of an affordable, small and light PTR-TOFMS instrument, complemented by an outstanding sensitivity.

The PTR-TOF 1000 *ultra* has industry-leading sensitivity thanks to the revolutionary ION-BOOSTER funnel technology and the new X2 option featuring an additional hexapole ION-GUIDE.

Quantitative analysis of the entire mass range in split-seconds and high mass resolution are features of all IONICON time-of-flight mass spectrometers. Direct injection of sample gas without preparation contributes to the speed and simplicity our instruments are known for.

The unique soft ionization (PTR) technology together with our extensive experience in gas-phase ion chemistry and engineering of scientific instruments are the basis for the reliability, ultra-low detection limit, fast response time and robustness of our PTR-MS systems.

- > ION-BOOSTER funnel technology
- > NEW: X2 Performance Option
- > Compact & affordable PTR-TOFMS
- > Entire mass range in split-seconds

Find out more:

www.ionicon.com/products

PTR-TOF 1000 **ULTRA**

ion
GUIDE
X2
BOOSTER


IONICON PTR-TOF 1000 *ultra* SPECIFICATIONS*

- Mass resolution: > 1500 m/Δm (FWHM) for m/z > 79
- Response time: < 100 ms
- Sensitivity: m/z 181 > 2000 cps/ppbv
- Limit of Detection: < 5 pptv (60 sec)
- X2** with X2 Performance Option:
 - Sensitivity: m/z 181 > 30000 cps/ppbv
 - Limit of Detection: < 5 pptv (10 sec)
- Mass range: 1-10000 amu
- Adjustable inlet flow: 50 - 800 sccm
- Inlet system (Different/Multiplexing inlet systems available on request):
 - 1.2 m long inlet hose - with inert (PEEK) capillary
 - Inlet system heating: 40-180°C (104-356°F)
 - Reaction chamber heating range: 40 - 120°C (104 - 248°F)
- Power requirements:
 - 115/230 V, standby/typical operation: < 400/550-850 W
- Dimensions (w x h x d): 60x91x80 cm (23.7x35.9x31.5 in.)
- Weight: < 130 kg (286.6 lbs)
- Interfaces: 8x DI/O, 2x AI, 2x AO
(digital/analog I/O package on request)

*Specifications are subject to change without prior notice.
Product pictures and illustrations may differ from actual configuration.
Detection limit, linearity range and resolution are dependent on the substances measured, integration time and system set-up.

PTR-TOF 1000 *ultra* BENEFITS

The PTR-TOF 1000 *ultra* combines the latest IONICON PTR-TOFMS evolution with the ION-BOOSTER funnel technology to perfection. In an ion funnel a RF-voltage focuses the ions through an array of ring electrodes, which improves ion transmission leading to a much higher sensitivity.



NEW: X2 Ultimate Performance Option

We now offer the possibility to push the PTR-TOF 1000 *ultra* beyond all limits with the new X2 option. X2 combines the ION-BOOSTER funnel with the unique IONICON hexapole ION-GUIDE for market-leading PTR-MS sensitivity of more than 30000 cps/ppbv, delivering low detection limits in incredible short integration times.

This makes the advantageous time-of-flight based instrument even more suited for high-speed applications, challenged by very low VOC concentrations, complex samples or a large number of sample compounds, where e.g. quadrupole based or lower sensitivity VOC analyzers fail to perform.

PTR-MS

We proudly rely on the unique IONICON PTR-MS soft ionization technology where by proton transfer from H₃O⁺, all compounds with a higher proton affinity (PA) than water are ionized. Common constituents of air, such as N₂, O₂, Ar, CO₂ etc. have lower PAs than H₂O and are therefore not detected. This is one of the main reasons for our market-leading low, real-time detection limit for trace compounds. Due to precisely controlled ion source and drift tube parameters, absolute quantification of VOC concentrations is possible.

SRI-MS

The IONICON PTR-TOF 1000 *ultra* is also available with Selective Reagent Ionization - Mass Spectrometry (SRI/SRI⁺), featuring NO⁺, O₂⁺ and NH₄⁺ (patent pending) or Kr⁺ (SRI⁺, US Pat. 9,188,564, EP 2606505 A1) alternatively to H₃O⁺ as precursor ions created in the IONICON ULTRA-PURE ion source.

O₂⁺, but especially Kr⁺, have a higher ionization potential than H₃O⁺ and therefore many important (inorganic) substances such as CH₄, CO, CO₂, NO₂, SO₂, etc. can be detected and quantified using a single IONICON instrument. NO⁺ as reagent ions help separating several isomeric VOCs for subsequent real-time analysis. NH₄⁺ offers improved selectivity, simplified mass spectra and suppressed fragmentation.

ROBUST, RELIABLE & EASY TO USE

The PTR-TOF 1000 *ultra* is completely software controlled. Installed in a space-saving rack and mounted on wheels, it allows for easy transportability and variable location measurements. We deliver the PTR-TOF 1000 *ultra* in a re-usable eco-friendly flightcase container.